



Datasheet of Model_ SCMR30A

Version D.



30-Port Smart USB Type-C Charging Trolley

CE Statement: This is a Class A product in the domestic environment, this product may cause radio interference, in which case the user may be required to take adequate measures.



SPECIFICATIONS

Model No.	SCMR30A
Features	Provides the storage space and the charging requirement with the 30-port Type-C sockets, up to 14-inch device
Display	LED Status Indicators: 1. Blue light flashes slowly : indicator the USB Type-C Port Slow charging 2. Blue light flashes quickly : indicator the USB Type-C Port Quick charging 3. Blue light off or steady on: indicator the Port has been charged (Depending on the charging status of the device) 4. Red light steady on: indicator single Port abnormal and cannot be charged
Power Supply	Input Outlet: AC 100V~240V, 50/60Hz, 5A (x3)
Output	USB Type-C PD3.0 PPS output x 30 Ports; each layer is 10 Ports, there are three layer in total and the voltage not over 720W Each port spec as below : 1. DC- 5V · max output current 3A · max power 15W 2. DC- 9V · max output current 3A · max power 27W 3. DC-12V · max output current 3A · max power 36W 4. DC-15V · max output current 3A · max power 45W 5. DC-20V · max output current 3.25A · max power 65W (Will reach max output current 5A · max power 100W in upcoming version) 6. PPS mode
Over-charging Protection	1.USB Type C, Over Current Protection (OCP) 2.USB Type C, Short-circuit Protection (SCP) 3.USB Type-C, Total DC Power Protection (TCP) 4. When the total power consumption exceeds the limit while using both the external outlet and the charging device simultaneously, the protection switch will be activated. At this time, all devices will enter a power-off protection mode. Please adjust the power usage mode to reduce the total power consumption, then reset the protection switch and power on again 5.When the malfunctions, the total output power will be temporarily reduced depending on the load condition.
Temperature Range	0 ~ 40°C (operating)
Temperature Range	-5 ~ 50°C (non-operating)
USB Type-C cable management	Independent Dividers and Cable management with nuts
Security	Front door with a 3-point security lock / back door with a security lock
Castors	4" swivel castors x4 (2 of castors are lockable)
Slot size	30 x 330 x 245 mm (WxDxH)
Dimension	530 x 500 x 1110 mm (WxDxH) (Castors included, handle is hidden)
Net Weight	51Kg
Gross Weight	56Kg
Certification	FCC/CE/CB